











## ACKNOWLEDGEMENTS

This work was supported by Zhejiang Sci-Tech University 521 talent cultivation program and Zhejiang provincial Natural Science Foundation of China (No. LY12E05028).

## REFERENCES

- [1] Zhao Y, Wu C, Hu X, Yu G. Research progress and problems of agricultural robot. *Trans Chin Soc Agric Eng* 2003; 19(1): 20-4.
- [2] Zhang L, Hu H, Ji S, Xu F. Review of non-destructive quality evaluation technology for fruit and vegetable products. *Trans Chin Soc Agric Eng* 2005; 21(4): 176-80.
- [3] Song J, Zhang T, Xu L, Tang X. Research actuality and prospect of picking robot for fruits and vegetables. *Trans Chin Soc Agric Mach* 2006; 37(5): 158-62.
- [4] Zhen Y, Zhang H, Chen W, Zhu ZC. A Full-drive Dexterous Manipulator. China. ZL201020666505, 2010.
- [5] Ma L, Yang W, Wang C, *et al.* Structure design and experiment of the end-effector for apple-harvesting robot. *J Agric Mech Res* 2009; (12): 65-7.
- [6] Hua D, Hua Z. Linkage mechanism design and application innovation. Beijing, China: Mechanical Industry Press 2007.
- [7] Monta M, Kondo N, Ting KC. End-effectors for tomato harvesting robot. *Artif Intell Rev* 1998; 12(1-3): 11-25.
- [8] Liu J, Li P, Li Z. Hardware design of the end-effector for tomato-harvesting robot. *Trans Chin Soc Agric Mach* 2008; 39(3): 109-12.
- [9] Xu L, Zhang T. Present situation of fruit and vegetable harvesting robot and its key problems and measures in application. *Trans Chin Soc Agric Eng* 2004; 20(5): 38-42.
- [10] Fon D, van Weel PA, Buwalda F. Development of a new tomato production system Research Station for Floriculture. *Trans Chin Soc Agric Mach* 1995; 3(1): 15-29.
- [11] Tang Z, Meng X, Shen C, *et al.* Design and experimental investigation of mechanical vibration tree fruits and nutsharvester. *J Agric Mech Res* 2010; 8: 56-9.
- [12] Liu C, Zhang T, Yang L. Design of End-effector of eggplant harvesting robot. *J Agric Mech Res* 2008; 12: 62-4.
- [13] Li X, Ren H. Motion analysis and application research on the underactuated mechanism. *Mech Res Appl* 2010; 23(12): 29-31.
- [14] Ying Y, Li Q, Wu C, *et al.* Underactuated Finger Device Has Properties of Preventing degradation 2007, China. ZL200710071186.
- [15] Birglen L, Gosselin CM. On the force capability of underactuated fingers. *Int Conf Robotics Automat, Taipei, Taiwan 2002*; pp. 1139-1145.
- [16] Birglen L, Gosselin CM. Geometric design of the two-phalanx underactuated finger. *ASME J Mech Des* 2006; 128(2): 333-364.
- [17] Mao Y, Zhu X, Li S, Yang F. Design of a new underactuated prosthetic hand. *Mach Des Res* 2008; 24(3): 33-36.
- [18] Luo M, Mei T, Wang X. Design of a simple semi-adaptive underactuated robot finger with three phalanges. *Comput Aided Des Comput Graph* 2005; 17(7): 355-3.
- [19] Luo M, Mei T, Lu C, Yu Y. Analysis and simulation of enveloping grasp stability of the multi-phalange underactuated robot hand. *Optics Precis Eng* 2005; 12(5): 51-7.
- [20] Cui P, Chen Z, Zhang J. Static analysis of apple-picking robot humanoid manipulator. *Trans Chin Soc Agric Mach* 2011; 42(2): 149-53.
- [21] Li Q, Hua D, Wang C, Hu X, Ying Y. Review of end-effectors in fruit and vegetable harvesting robot. *Trans Chin Soc Agric Mach* 2008; 39(3): 109-9.

Received: April 14, 2015

Revised: May 21, 2015

Accepted: May 25, 2015

© Ya-xin *et al.*; Licensee Bentham Open.

This is an open access article licensed under the terms of the Creative Commons Attribution Non-Commercial License (<http://creativecommons.org/licenses/by-nc/3.0/>) which permits unrestricted, non-commercial use, distribution and reproduction in any medium, provided the work is properly cited.